


Technical Data Sheet

GSF15 (L)

» Special liquids



GSF15 (L)
single acting, single air drive head with distance piece
(Standard= Bottom inlet)

Technical Data:

Air drive pressure:	1-10 bar / 14,5 - 145psi
Calculated Outlet Pressure at an air drive of 10 bar/145 psi:	160 bar/ 2,320 psi
Pressure ratio:	1:16
Displacement volume/double stroke	62.0 cm ³ / 3.78 cu.inch

Connections:

Inlet:	Standard: Bottom Inlet 1 BSP
Outlet:	3/4 BSP
Air drive:	3/4 BSP
Maximum operating temperature:	60°C
Net weight:	20.0 kg

Pressure and flow performances, please see enclosed graph.

Wetted materials of construction:

Seal package:	GSF15(L): Polyurethan, NBR GSF15(L)VE: UHMWPE, FKM
Pump Body:	1.4305
Piston:	1.4112 (hardened)
Fittings:	1.4571

Approximate Dimensions:

Height:	411 mm
Depth:	190.5 mm
Width:	272 mm

Available Options:

Side inlet	GSF15(L)S
Special inlet and outlet ports, i.e. NPT	GSF15(L)-NPT

Special seal material to handle special fluids on request.

Available Accessories:

Air control units with filter pressure regulator, control pressure gauge and shut off valve:	GSF15(L) with C2
To protect the pump against excessive outlet pressures or to limit the outlet pressure, a safety valve can be fitted to the air control unit in the air drive line:	GSF15(L) with C2/SVair (The required outlet pressure has to be indicated.)

Please consult factory for more information. All technical and dimensional information subject to change. All General Terms and Conditions of sale, including limitations of our liability, apply to all products and services sold.

Leistungsdiagramm/Performance Graph G(SF) 15

Prüfflüssigkeit/Test Liquid: Wasser-Öl-Emulsion/Water Oil Emulsion ca. 1 - 10 cst

